



Marketing Specification

F5RL Series Notebook PC

A Revolutionary Notebook for Virtual Office

5 Pages









Processor & Cache (Pls use "Marketing name")

Intel® Core™ 2 Duo Processor T5x50 Processor up to 667MHz FSB

Intel® Pentium Dual Core Processor T2330/T2310

Intel Celeron M Processor (Merom Based, socket P) (C-M 550/540)

* Intel's numbering is not a measurement of higher performance.

NOTE: Processor speed denotes maximum performance mode; processors will run at lower speeds in battery optimization mode.

Operating System

Preinstalled

Genuine Windows® Vista™

- Genuine Home Basic
- Genuine Home Premium
- Genuine Business

Supported Microsoft® Windows® XP, SP2

Chipset

ATI Radeon Xpress 1100 (RC415M + SB600)

BIOS



AMI BIOS code; 4Mb Flash EPROM

Boot from USB LAN and AI-Flash 3, AI-Flash 4, AI-Flash 5

Main Memory

Standard 512-MB, 1024-MB 667-MHz DDR2 SDRAM; two SODIMM slots supporting single channel memory

Maximum Upgradeable to 2048-MB maximum (1024-MB SODIMM in slots 1 and 2)

Single-Channel DDR2 533/667 DRAM support

NOTE: Vista 32bit standard of memory modules at least 512-MB(and above). If you mix memory speeds, the system will perform at the lower memory speed. Above 3-GB, all memory may not be available due to system resource requirements.

Display

Internal 15.4-inch WXGA (1280 x 768 resolution and 16 M colors)

External 15.4-inch WXGA+ wide viewing angle (1440 x 900 resolution and 16 M colors)

Up to 32-bit per pixel color depth

VGA port supports resolutions up to 2048 x 1536 at 75 Hz, and lower resolutions at up to 100 Hz

NOTE: Resolutions are dependent upon monitor capability, and resolution and color depth settings.

Graphics & Video Module

Integrated graphics core derivative of Radeon® X1100 technology Hyper memory support

Display

VGA 640 x 480 256/64K/16.7M colors SVGA 800 x 600 256/64K/16.7M colors XGA 1024 x 768 256/64K/16.7M colors UXGA 1600 x1200 256/64K/16.7M colors

Multi-Card Reader

7 in 1, Supports SD (Secure Digital), MMC (MultiMedia Card), Memory Stick, Memory Stick Pro, Memory Stick Duo*, Smart Media, xD-Picture card

*NOTE: Memory Stick Duo Adapters are required and sold separately. Inserting a Memory Stick Duo

Card directly into your notebook could damage the memory card and/or notebook.

Hard Disk Drive

200-GB 4200 rpm SATA

160-GB 5400 rpm SATA

120-GB 5400 rpm SATA

80-GB 5400 rpm SATA

Support Hybird Disc

NOTE: These hard drives are customer removable and will withstand multiple insertion/removal cycles.

Up to 8 GB is reserved for the system recovery software.

Expansion Card Slots

Express Card slot Express Card/34 or ExpressCard/54



Camera

1.3M pixels CMOS Camera (Optional)

Keyboard

19 mm full size 88key with MS-Windows function keys

2.5mm travel

Add VISTA K/B Start Button

Optical Storage Device

Interchangeable 5.25" optical drive; CTO option(12.7mm) 24X/24X/8X/24X DVD+CD- RW Combo module

Interchangeable 5.25" ATAPI 8X/4X, DVD+R/RW: 8X/4X, CD-R/RW:24X/10X, DVD-ROM:8X, CD-ROM:

Network Connectivity

Integrated 802.11B/G WLAN and 802.11n WLAN (BTO) (Mini Card PCI-e)

Integrated MDC Fax/ Modem (ASUS)

On board 10/100 Mbps Fast Ethernet Controller

Support Wake-On-LAN on S4 AC-In Mode only

Worldwide Regulation, MODEM supported V.92 and Universal PPT (CTR 21, JATE, FCC, A-tick, DGT, 中國入網許可)

Wireless Certification System: TWN, CHN, FCC, European

Interface

PC Card Slot New card support

Express Card Slot Express Card/34 or ExpressCard/54

External Monitor One – VGA

External Microphone One
Headphone/Line out One
Power Connector One
RJ-11 (Modem) One
RJ-45 (NIC) One
USB 2.0 Four
LED Status Indicators FINE

LED Status Indicator

Power On/ Suspend/ Battery Full, Charging, Low/ Bluetooth/ WLAN Accessing/ Storage device access/ Caps Lock/ Number Lock/ Scroll lock

Audio

Integrated Azalia compliant audio chip, with 3D effect & full duplex ALC 660D)

SoundBlaster Pro Compatible

Build-in stereo speakers

Power Management

Full feature SMI power management, Stand-by, Suspend to Disk, and Suspend to RAM



ACPI 1.0b and 2.0(partially) supported MDP 2003 compatible Support New Battery charging policy

Battery

Battery Pack Li-lon 49 WHrs (6 cell: 4400mAh, 3S2P) & Li-lon 36 WHrs (4 cell: 2200mAh, 4S1P)

&Life Run-Down life:>2.5hr

Smart battery, charging time, TBD

(System On/Off) to 95%

NOTE: Battery life will vary depending on the product configuration, product model, applications loaded on the product, power management settings of the product, and the product features used by the customer.

As with all batteries, the maximum capacity of this battery will decrease with time and usage.

Power Supply

External 65-watt AC adapter Output: 19V DC, 3.72A, 65W

Input: 100~240V AC, 50/60Hz universal

2/3 pin power supply system

Pointing Device

Built-in Touch pad pointing device

2 click buttons with scroll key

Support Pad-Lock Function (Hot Key on/off)

Touch pad with Numeral function

Heat Dissipation

ADTD (Developed by Asus) to handle 31W CPU thermal envelope

Dimensions (WxDxH) 365~367 x 262 x 27(front)~35(rear)mm

Weight 2.65 Kg with 15.4-inch display and 6 cell batt.

NOTE: Height varies depending upon where on the notebook the measurement is made. Weight varies by configuration and components.

Security

- TPM 1.2 (Optional)
- Pre-OS Authentication by programmable key code
- BIOS Booting User Password Protection
- HDD User Password Protection and Security Lock
- Kensington Lock hole provided

Software Utility



Asus Built or modified for Vista

- Asus Win flash for BIOS and Driver live Update
- Power4Gear+: Pre-defined power saving theme
- Asus Screen Saver
- Asus Live Update
- Asus Life frame II
- Net 4 switch
- Multi-Frame
- Power 4 Phone
- Color Enhancement (Splendid)
- ASUS Wireless Console
- Instant Fun PLUS

Shipment bundle S/W:

- Norton 2007
- Adobe Acrobat Reader 8.0
- Nero V7.x (Bundle with CD/DVD recorder)

ASUSDVD /Cyber link Power DVD (w/ DVD model) w/ latest qualified version

Industry Standard Certifications

- EMI: USA(FCC-B), JAP(VCCI-B), TWN, CCC
- Safety: CE, CB, cUL, CCC,

Modem: Universal PPT including US (FCC-68), TWN (DGT), PRC, JPN (JATE), EURO (CTR21)